

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

1-4. (Cancelled)

5. (Currently Amended) A display comprising:

organic light-emitting diode structures forming an array, each of the organic light-emitting diode structures comprising:

first and second anodes;

first and second organic light-emitting layers disposed between the first and the second anodes; and

a common electrode disposed between the first and the second organic light-emitting layers[.];

a first transistor coupled to each of the organic light-emitting diode structures, the first transistor coupled to one of the first and the second anodes of the organic light-emitting diode structures;

a second transistor coupled to each of the organic light-emitting diode structures, the second transistor coupled to the other one of the first and the second anodes of the organic light-emitting diode structures; and

a third transistor coupled to the first and the second transistors, the third transistor for switching the first and second transistors,

wherein the first organic light-emitting layer is for substantially emitting light in a first direction and the second organic light-emitting layer is for substantially emitting light in a second direction opposite to the first direction.

6-8. (Cancelled)

9. (Currently Amended) The display according to claim 5, wherein the first and the second transistors drive the organic light-emitting diode structures.

10. (Cancelled)

11. (Original) The display according to claim 5, wherein light is emitted from at least one of the first and the second organic light-emitting layers when an electric current passes between one of the first and the second anodes and the first electrode.

12-13. (Canceled)

14. (Currently Amended) A telecommunication device comprising:

a main body;

a flip-up door connected to the main body; and

a display beneath the flip-up door, the display comprising:

organic light-emitting diode structures forming an array, each of the organic light-emitting diode structures comprising:

first and second anodes;

first and second organic light-emitting layers disposed between the first and the second anodes; and

a common electrode disposed between the first and second organic light-emitting layers[.];

a first transistor coupled to each of the organic light-emitting diode structures, the first transistor coupled to one of the first and the second anodes of the organic light-emitting diode structures;

a second transistor coupled to each of the organic light-emitting diode structures, the second transistor coupled to the other one of the first and the second anodes of the organic light-emitting diode structures; and

a third transistor coupled to the first and the second transistors, the third transistor for switching the first and second transistors.

wherein the first organic light-emitting layer is for substantially emitting light in a first direction and the second organic light-emitting layer is for substantially emitting light in a second direction opposite to the first direction.

U.S. Serial No. 10/829,317

Responsive to final Office Action mailed December 20, 2006

15-18. (Cancelled)